



Ref.

HLX12. LEG012

Colección / Collection / Collection

Technical Indoor. PRO Professional LED

Descripción / Description / Description

Módulo LED COB. Driver externo incluido
COB LED Module. Ext. driver included
Module LED COB. Driver externe inclus

Características Luminaria / Light Data Sheet / Caractéristiques de la Luminaire

Material / Material / Matériau	Aluminio / Aluminium / Aluminium		
Material Difusor / Difusor Material / Matériau Diffuseur	PC		
Acabado Difusor / Diffuser Finish/ Touche Finale du Diffuseur	Transparente / Transparent / Transparent		
Vatios / Watts / Watts	12W		
Lúmens / Lumens / Lumens	Color T. ^a	Useful Lm	Chip Lm
	2700K	1207 lm	1572 lm
	3000K	1238 lm	1620 lm
	4000K	1300 lm	1656 lm
Grados Apertura / Opening Angle / Angle d'ouverture	60°		
IP	20		
Tiempo de Uso (h/día) / Working Time (h/day) / Temps d'utilisation (h/jour)	12-14		
On/Off	15.000		
Temperatura de Funcionamiento (Ta) / Working Temperature (Ta) / Température de Fonctionnement (Ta)	-20°C to +45°C		
Humedad de Funcionamiento / Working Humidity / Humidité de Fonctionnement	20-90% RH		
Peso / Weight / Poids			
Cantidad / Pieces / Quantité	1/ 50		

Características del Chip / Chip Data Sheet / Caractéristiques de la Puce

Marca / Brand / Marque	EDISON
Tipo / Type / Type	COB
L70B10	50.000 h
SDCM (Mac Adam)	3
EN62471	RG1
Eficiencia Nominal / Nominal Efficiency / Efficacité Nominal	138 Lm/W (4000K)

Características Driver / Driver Data Sheet / Caractéristiques de l'Alimentateur

Ref.	Driver	Voltaje de Entrada Input Voltage Tension d'Entrée	FP PF FP	Garantía Warranty Garantie	Intensidad de Funcionamiento Working Current Courant de Fonctionnement	Flicker
HLX12-215_-	ON-OFF. Non Dimmable	AC220-240V 50/60Hz	>0,95	5	300 mA	Free
HLX12-235_-	ON-OFF. Non Dimmable	AC220-240V 50/60Hz	>0,95	5	300 mA	Free
HLX12-475_-	Dimmable. 1-10V/DALI/PUSH	AC200-240V 50/60Hz	>0,9	5	300 mA	Free
HLX12-515_-	Dimmable. Trailing Edge	AC220-240V 50/60Hz	>0,9	5	250 mA	Free

SMART CONTROL See page. 72 PRO Professional Catalog



Accesorios / Accessories / Accessoires



HCHLX



JISO Smart Control



2DCLEDK1



2DCLEDK2

Productos Relacionados / Related Products / Produits Associés



HLX08

Documentos / Documents / Des documents

Declaración de Conformidad UE / EU Declaration of Conformity / Déclaration de Conformité UE

http://www.jisoiluminacion.es/CE/Empotrables_D.pdf

Instrucciones de Instalación / Installation Instructions / Instructions d'Installation

http://www.jisoiluminacion.es/Instrucciones/HLX_1.pdf

Ficheros Fotométricos LDT / Photometrics File LDT / Fichier Photométrique LDT

http://www.jisoiluminacion.es/Ficheros_LDT/HLX12_LDT.zip

Ficheros Fotométricos IES / Photometrics File IES / Fichier Photométrique IES

http://www.jisoiluminacion.es/Ficheros_IES/HLX12_IES.zip