

## Ref.

**32128**

Colección / Collection / Collection

Technical Indoor. PRO Professional LED

Descripción / Description / Description

Panel LED. Backlight  
LED Panel. Backlight  
Panneau LED. Backlight

## Características Luminaria / Light Data Sheet / Caractéristiques de la Luminaire

Material / Material / Matériau	Aluminio / Aluminium / Aluminium		
Material Difusor / Difusor Material / Matériau Diffuseur	PMMA		
Acabado Difusor / Diffuser Finish/ Touche Finale du Diffuseur	Ácido / Acid / Acide		
Colores / Colours / Couleurs	90 Blanco Técnico / Technical White / Blanc Technique		
Vatios / Watts / Watts	28W		
Lúmens / Lumens / Lumens	Color T. <sup>a</sup>	Useful Lm	Chip Lm
	4000K	2465 lm	3417 lm
Grados Apertura / Opening Angle / Angle d'ouverture	120°		
IP	Ext 44 Int 20		
IK	02		
Tiempo de Uso (h/día) / Working Time (h/day) / Temps d'utilisation (h/jour)	12-14		
On/Off	15.000		
Temperatura de Funcionamiento (Ta) / Working Temperature (Ta) / Température de Fonctionnement (Ta)	-20°C to +45°C		
Humedad de Funcionamiento / Working Humidity / Humidité de Fonctionnement	20-90% RH		
Peso / Weight / Poids	Kg		
Cantidad / Pieces / Quantité	1/5		


## Características del Chip / Chip Data Sheet / Caractéristiques de la Puce

Marca / Brand / Marque	SANAN
Tipo / Type / Type	SMD 2835
L80 B10	54.000 h
SDCM (Mac Adam)	5
EN62471	RG1
Eficiencia Nominal / Nominal Efficiency / Efficacité Nominal	136 Lm/W (4000K)

## Características Driver / Driver Data Sheet / Caractéristiques de l'Alimentateur

Ref.	Driver	Voltaje de Entrada Input Voltage Tension d'Entrée	FP PF FP	Garantía Warranty Garantie	Intensidad de Funcionamiento Working Current Courant de Fonctionnement	Flicker
32128-218_-	ON-OFF. Non Dimmable	AC220-240V 50/60Hz	>0,95	5	700 mA	Free

## Colores / Colours / Couleurs



90 Blanco Técnico / Technical White  
/ Blanc Technique

## Accesorios / Accessories / Accessoires



2DCLEDK1



2DCLEDK2



DC31036-2



DC30140-3



DC32140-4



DC12030-4




DC31036-1




DC31640-0


## Productos Relacionados / Related Products / Produits Associés



39137



32140



32740

## Documentos / Documents / Des documents

Declaración de Conformidad UE / EU Declaration of Conformity / Déclaration de Conformité UE

[http://www.jisoiluminacion.es/CE/Empotrables\\_D.pdf](http://www.jisoiluminacion.es/CE/Empotrables_D.pdf)

Instrucciones de Instalación / Installation Instructions / Instructions d'Installation

[http://www.jisoiluminacion.es/Instrucciones/32\\_I.pdf](http://www.jisoiluminacion.es/Instrucciones/32_I.pdf)

Ficheros Fotométricos LDT / Photometrics File LDT / Fichier Photométrique LDT

[http://www.jisoiluminacion.es/Ficheros\\_LDT/32128\\_LDT.zip](http://www.jisoiluminacion.es/Ficheros_LDT/32128_LDT.zip)

Ficheros Fotométricos IES / Photometrics File IES / Fichier Photométrique IES

[http://www.jisoiluminacion.es/Ficheros\\_IES/32128\\_IES.zip](http://www.jisoiluminacion.es/Ficheros_IES/32128_IES.zip)

Este producto contiene una fuente luminosa de la clase de eficiencia energética D.

This product contains a light source of energy efficiency class D.

Ce produit contient une source lumineuse de classe d'efficacité énergétique D.