



Ref.

3100-2924V

Colección / Collection / Collection

Technical Indoor. PRO Professional

Descripción / Description / Description

Power Supply ON/OFF

Características / Data Sheet / Caractéristiques

Material / Material / Matériau	Metal / Metal / Métal
Serie	JISO
Input voltage	100-120V/200-240V
Vatios / Watts / Watts	100W
Tiempo de Uso (h/día) / Working Time (h/day) / Temps d'utilisation (h/jour)	12-14
On/Off	15.000
Temperatura de Funcionamiento (Ta) / Working Temperature (Ta) / Température de Fonctionnement (Ta)	-20°C ~ +60°C
Humedad de Funcionamiento / Working Humidity / Humidité de Fonctionnement	20-90% RH
Voltaje de Entrada / Input Voltage / Tension d'Entrée	24 Vdc 50/60Hz
FP / PF	> 0,5
Intensidad de Funcionamiento / Working Current / Courant de Fonctionnement	4170 mA
Tension d'Entrée	NOT-Free
Size	L159 x A98 x H38 mm

Compatibilidades entre fuentes de alimentación y tiras led dependiendo de la longitud

Compatibilities between power supplies and led strips depending on the lenght

Compatibilités entre les sources d'alimentation et les bandes LED en fonction de la longueur

MODELO	POWER (W/m)	VOLTAGE (V)	2m < L ≤ 3m	3m < L ≤ 4m	4m < L ≤ 5m	6m < L ≤ 7m	7m < L ≤ 8m
90009	9,6	24	-	-	-	3100-2924V 9.6.x7x1.2=80.64W	3100-2924V 9.6.x8x1.2=92.16W
90014	14,4	24	-	-	3100-2924V 14.4x5x1.2=86.4W	-	-
90018	18	24	-	3100-2924V 18x4x1.2=86.4W	-	-	-
90019	19,2	24	-	3100-2924V 19.2x4x1.2=92.2W	-	-	-
90024	24	24	3100-2924V 24x3x1.2=86.4W	-	-	-	-