



## Ref.

**3050-2924V**

Colección / Collection / Collection	Technical Indoor: PRO Professional
Descripción / Description / Description	Power Supply ON/OFF

## Características / Data Sheet / Caractéristiques

Material / Material / Matériau	Metal / Metal / Métal
Serie	JISO
Input voltage	100-120V/200-240V
Vatios / Watts / Watts	50W
Tiempo de Uso (h/día) / Working Time (h/day) / Temps d'utilisation (h/jour)	12-14
On/Off	15.000
Temperatura de Funcionamiento (Ta) / Working Temperature (Ta) / Température de Fonctionnement (Ta)	-20°C ~ +60°C
Humedad de Funcionamiento / Working Humidity / Humidité de Fonctionnement	20-90% RH
Voltaje de Entrada / Input Voltage / Tension d'Entrée	24 Vdc 50/60Hz
FP / PF	> 0,5
Intensidad de Funcionamiento / Working Current / Courant de Fonctionnement	2500 mA
Tension d'Entrée	NOT-Free
Size	L111 x A78 x H36 mm

Compatibilidades entre fuentes de alimentación y tiras led dependiendo de la longitud

Compatibilities between power supplies and led strips depending on the lenght

Compatibilités entre les sources d'alimentation et les bandes LED en fonction de la longueur

MODELO	POWER (W/m)	VOLTAGE (V)	1m < L ≤ 2m	3m < L ≤ 4m	6m < L ≤ 7m	7m < L ≤ 8m
90004	4,8	24	-	-	<b>3050-2924V</b> 4.8x7x1.2=40.32W	<b>3050-2924V</b> 4.8x8x1.2=46.08W
90009	9,6	24	-	<b>3050-2924V</b> 9.6.x4x1.2=46.1W	-	-
90018	18	24	<b>3050-2924V</b> 18x2x1.2=43.2W	-	-	-
90019	19,2	24	<b>3050-2924V</b> 19.2x2x1.2=46.1W	-	-	-