

Ref.

53724

Colección / Collection / Collection	Technical Indoor. PRO Professional LED
Descripción / Description / Description	Downlight LED Downlight LED Downlight LED

Características Luminaria / Light Data Sheet / Caractéristiques de la Luminaire

Material / Material / Matériau	Aluminio / Aluminium / Aluminium		
Material Difusor / Difusor Material / Matériau Diffuseur	PMMA		
Acabado Difusor / Diffuser Finish / Touche Finale du Diffuseur	Ácido / Acid / Acide		
Colores / Colours / Couleurs	90 Blanco Técnico / Technical White / Blanc Technique		
Vatios / Watts / Watts	24W		
Lúmens / Lumens / Lumens	Color T. ^a	Useful Lm	Chip Lm
	3000K	2201 lm	2916 lm
	4000K	2217 lm	2916 lm
Grados Apertura / Opening Angle / Angle d'ouverture	100°		
IP	Ext 65 Int 20		
Tiempo de Uso (h/día) / Working Time (h/day) / Temps d'utilisation (h/jour)	12-14		
On/Off	15.000		
Temperatura de Funcionamiento (Ta) / Working Temperature (Ta) / Température de Fonctionnement (Ta)	-20°C to +40°C		
Humedad de Funcionamiento / Working Humidity / Humidité de Fonctionnement	20-85% RH		
Peso / Weight / Poids			
Cantidad / Pieces / Quantité	1/20		

Características del Chip / Chip Data Sheet / Caractéristiques de la Puce

Marca / Brand / Marque	SANAN
Tipo / Type / Type	SMD 2835
L70 B10	50.000 h
SDCM (Mac Adam)	5
EN62471	RG1
Eficiencia Nominal / Nominal Efficiency / Efficacité Nominal	120 Lm/W (4000K)

Características Driver / Driver Data Sheet / Caractéristiques de l'Alimentateur

Ref.	Driver	Voltaje de Entrada Input Voltage Tension d'Entrée	FP PF FP	Garantía Warranty Garantie	Intensidad de Funcionamiento Working Current Courant de Fonctionnement	Flicker
53724-218_-	ON-OFF. Non Dimmable	AC220-240V 50/60Hz	>0,9	5	700 mA	Free
53724-238_-	ON-OFF. Non Dimmable	AC220-240V 50/60Hz	>0,95	5	700 mA	Free
53724-478_-	Dimmable. DALI, PUSH, 1-10V	AC200-240V 50/60Hz	>0,95	5	700 mA	Free
53724-518_-	Dimmable. Trailing Edge	AC220-240V 50/60Hz	>0,9	5	700 mA	Free


SMART CONTROL See page. 72 PRO Professional Catalog

Colores / Colours / Couleurs



90 Blanco Técnico / Technical White
/ Blanc Technique

Accesorios / Accessories / Accessoires



JISO Smart Control



2DCLEDK1



2DCLEDK2

Productos Relacionados / Related Products / Produits Associés



53710

Documentos / Documents / Des documents

Declaración de Conformidad UE / EU Declaration of Conformity / Déclaration de Conformité UE

http://www.jisoiluminacion.es/CE/Empotrables_D.pdf

Instrucciones de Instalación / Installation Instructions / Instructions d'Installation

http://www.jisoiluminacion.es/Instrucciones/535-537_I.pdf

Ficheros Fotométricos LDT / Photometrics File LDT / Fichier Photométrique LDT

http://www.jisoiluminacion.es/Ficheros_LDT/53724_LDT.zip

Ficheros Fotométricos IES / Photometrics File IES / Fichier Photométrique IES

http://www.jisoiluminacion.es/Ficheros_IES/53724_IES.zip