



**Ref.**

**53533**

Colección / Collection / Collection Technical Indoor. PRO Professional LED

Descripción / Description / Description  
Downlight LED  
Downlight LED  
Downlight LED

**Características Luminaria / Light Data Sheet /  
Caractéristiques de la Luminaire**

Material / Material / Matériau	Aluminio / Aluminium / Aluminium		
Material Difusor / Difusor Material / Matériau Diffuseur	Cristal / Glass / Verre		
Acabado Difusor / Diffuser Finish / Touche Finale du Diffuseur	Transparente / Transparent / Transparent		
Colores / Colours / Couleurs	01 Negro / Black / Noir 90 Blanco Técnico / Technical White / Blanc Technique		
Vatios / Watts / Watts	30W		
Lúmens / Lumens / Lumens	Color T. <sup>a</sup>	Useful Lm	Chip Lm
	3000K	3000 lm	3562 lm
	4000K	3150 lm	3640 lm
Grados Apertura / Opening Angle / Angle d'ouverture	60°		
IP	Ext 65	Int 20	
Tiempo de Uso (h/día) / Working Time (h/day) / Temps d'utilisation (h/jour)	12-14		
On/Off	15.000		
Temperatura de Funcionamiento (Ta) / Working Temperature (Ta) / Température de Fonctionnement (Ta)	-20°C to +45°C		
Humedad de Funcionamiento / Working Humidity / Humidité de Fonctionnement	20-90% RH		
Peso / Weight / Poids			
Cantidad / Pieces / Quantité	1/12		

**Características del Chip / Chip Data Sheet / Caractéristiques de la Puce**

Marca / Brand / Marque	EDISON
Tipo / Type / Type	COB
L70B10	50.000 h
SDCM (Mac Adam)	3
EN62471	RG0
Eficiencia Nominal / Nominal Efficiency / Efficacité Nominal	121 Lm/W (4000K)



**Características Driver / Driver Data Sheet / Caractéristiques de l'Alimentateur**

Ref.	Driver	Voltaje de Entrada Input Voltage Tension d'Entrée	FP PF FP	Garantía Warranty Garantie	Intensidad de Funcionamiento Working Current Courant de Fonctionnement	Flicker
53533-215_-	ON-OFF. Non Dimmable	AC220-240V 50/60Hz	>0,95	5	700 mA	Free
53533-235_-	ON-OFF. Non Dimmable	AC220-240V 50/60Hz	>0,95	5	700 mA	Free
53533-475_-	Dimmable. DALI, PUSH	AC200-240V 50/60Hz	>0,95	5	700 mA	Free
53533-515_-	Dimmable. Trailing Edge	AC220-240V 50/60Hz	>0,9	5	700 mA	Free

SMART CONTROL See page. 72 PRO Professional Catalog

## Colores / Colours / Couleurs



90 Blanco Técnico / Technical White  
/ Blanc Technique

## Accesorios / Accessories / Accessoires



JISO Smart Control

2DCLEDK1

2DCLEDK2

## Productos Relacionados / Related Products / Produits Associés



53505



53510



53515



53533



53530 / 53540

## Documentos / Documents / Des documents

Declaración de Conformidad UE / EU Declaration of Conformity / Déclaration de Conformité UE

[http://www.jisoiluminacion.es/CE/Empotrables\\_D.pdf](http://www.jisoiluminacion.es/CE/Empotrables_D.pdf)

Instrucciones de Instalación / Installation Instructions / Instructions d'Installation

[http://www.jisoiluminacion.es/Instrucciones/535-537\\_I.pdf](http://www.jisoiluminacion.es/Instrucciones/535-537_I.pdf)

Ficheros Fotométricos LDT / Photometrics File LDT / Fichier Photométrique LDT

[http://www.jisoiluminacion.es/Ficheros\\_LDT/53533\\_LDT.zip](http://www.jisoiluminacion.es/Ficheros_LDT/53533_LDT.zip)

Ficheros Fotométricos IES / Photometrics File IES / Fichier Photométrique IES

[http://www.jisoiluminacion.es/Ficheros\\_IES/53533\\_IES.zip](http://www.jisoiluminacion.es/Ficheros_IES/53533_IES.zip)