

## Ref.

**00436-86**

Colección / Collection / Collection

Industrial. PRO Professional LED

Descripción / Description / Description


Pantalla Estanca LED  
LED Waterproof Screen  
Panneau LED Étanche

## Características Luminaria / Light Data Sheet / Caractéristiques de la Luminaire


Material / Material / Matériau	PC		
Material Difusor / Difusor Material / Matériau Diffuseur	PC		
Acabado Difusor / Diffuser Finish/ Touche Finale du Diffuseur	Ácido / Acid / Acide		
Colores / Colours / Couleurs	90 Blanco Técnico / Technical White / Blanc Technique		
Vatios / Watts / Watts	36W		
Lúmens / Lumens / Lumens	Color T. <sup>a</sup>	Useful Lm	Chip Lm
	4000K	4735 lm	5040 lm
Grados Apertura / Opening Angle / Angle d'ouverture	120°		
IP	IP65		
IK	08		
Tiempo de Uso (h/día) / Working Time (h/day) / Temps d'utilisation (h/jour)	12-14		
On/Off	15.000		
Temperatura de Funcionamiento (Ta) / Working Temperature (Ta) / Température de Fonctionnement (Ta)	-25°C to +40°C		
Humedad de Funcionamiento / Working Humidity / Humidité de Fonctionnement	20-80% RH		
Diametro de cable / Cable diameter / Diamètre de câble	Ø 8 /12 mm		
Medida cable / Cable size / Mesure de câble	1,5mm <sup>2</sup>		

## Características del Chip / Chip Data Sheet / Caractéristiques de la Puce

Marca / Brand / Marque	SANAN
Tipo / Type / Type	SMD 2835
L70 B10	50.000 h
SDCM (Mac Adam)	5
EN62471	RG1
Eficiencia Nominal / Nominal Efficiency / Efficacité Nominal	140 Lm/W (4000K)



## Included



## Características Driver / Driver Data Sheet / Caractéristiques de l'Alimentateur

Ref.	Driver	Voltaje de Entrada Input Voltage Tension d'Entrée	FP PF FP	Garantía Warranty Garantie	Intensidad de Funcionamiento Working Current Courant de Fonctionnement	Flicker
00436-86_-	ON-OFF. Non Dimmable + Emergency kit (3h aut.)	AC220-240V 50/60Hz	>0,9	5	350 mA	Not Free

## Colores / Colours / Couleurs



90 Blanco Técnico / Technical White  
/ Blanc Technique

## Productos Relacionados / Related Products / Produits Associés



00420



00450

## Continuous connection



### Double sides



### Security



### Stainless Steel Clips



## Documentos / Documents / Des documents

Declaración de Conformidad UE / EU Declaration of Conformity / Déclaration de Conformité UE

[http://www.jisoiluminacion.es/CE/Pantallas-Estancas\\_D.pdf](http://www.jisoiluminacion.es/CE/Pantallas-Estancas_D.pdf)

Instrucciones de Instalación / Installation Instructions / Instructions d'Installation

[http://www.jisoiluminacion.es/Instrucciones/004\\_I.pdf](http://www.jisoiluminacion.es/Instrucciones/004_I.pdf)

Ficheros Fotométricos LDT / Photometrics File LDT / Fichier Photométrique LDT

[http://www.jisoiluminacion.es/Ficheros\\_LDT/00436\\_LDT.zip](http://www.jisoiluminacion.es/Ficheros_LDT/00436_LDT.zip)

Ficheros Fotométricos IES / Photometrics File IES / Fichier Photométrique IES

[http://www.jisoiluminacion.es/Ficheros\\_IES/00436\\_IES.zip](http://www.jisoiluminacion.es/Ficheros_IES/00436_IES.zip)

*Este producto contiene una fuente luminosa de la clase de eficiencia energética D.*

*This product contains a light source of energy efficiency class D.*

*Ce produit contient une source lumineuse de classe d'efficacité énergétique D*