



**Ref.**

**05200-38**

Colección / Collection / Collection	Industrial. PRO Professional LED
Descripción / Description / Description	Campana Industrial LED Industrial LED High Bay Suspension Tertiaire LED

**Características Luminaria / Light Data Sheet /  
Caractéristiques de la Luminaire**

Material / Material / Matériau	Aluminio / Aluminium / Aluminium		
Material Difusor / Difusor Material / Matériau Diffuseur	PC		
Acabado Difusor / Diffuser Finish/ Touche Finale du Diffuseur	Transparente / Transparent / Transparent		
Colores / Colours / Couleurs	01 Negro / Black / Noir		
Vatios / Watts / Watts	200W		
Lúmens / Lumens / Lumens	Color T. <sup>a</sup>	Useful Lm	Chip Lm
	4000K	26183 lm	27000 lm
Grados Apertura / Opening Angle / Angle d'ouverture	01	120°	
	01-R00	90°	
	01-E00	60°	
IP	IP65		
IK	08		
Tiempo de Uso (h/día) / Working Time (h/day) / Temps d'utilisation (h/jour)	12-14		
On/Off	15.000		
Temperatura de Funcionamiento (Ta) / Working Temperature (Ta) / Température de Fonctionnement (Ta)	-20°C to +45°C		
Humedad de Funcionamiento / Working Humidity / Humidité de Fonctionnement	10-95% RH		
Peso / Weight / Poids	2,85 Kg		
Cantidad / Pieces / Quantité	1		

**Características del Chip / Chip Data Sheet / Caractéristiques de la Puce**

Marca / Brand / Marque	SANAN
Tipo / Type / Type	SMD 3030
L70 B10	50.000 h
SDCM (Mac Adam)	5
EN62471	RG0
Eficiencia Nominal / Nominal Efficiency / Efficacité Nominal	135 Lm/W (4000K)

**Características Driver / Driver Data Sheet / Caractéristiques de l'Alimentateur**

Ref.	Driver	Voltaje de Entrada Input Voltage Tension d'Entrée	FP PF FP	Garantía Warranty Garantie	Intensidad de Funcionamiento Working Current Courant de Fonctionnement	Flicker
05200-3884-	Dimmable 0-10V	AC220-240V 50/60Hz	>0,95	5	1450 mA	Free

### Colores / Colours / Couleurs



01 Negro / Black / Noir

### Accesorios / Accessories / Accessoires



CONECIP67I03



DCP05240-01



DC05DALI



60°



90°



120°

DC05200

### Productos Relacionados / Related Products / Produits Associés



05100



05150



05240

### Documentos / Documents / Des documents

Declaración de Conformidad UE / EU Declaration of Conformity / Déclaration de Conformité UE

<http://www.jisoiluminacion.es/CE/CE-FLOODLIGHT.pdf>

Instrucciones de Instalación / Installation Instructions / Instructions d'Installation

<http://www.jisoiluminacion.es/Instrucciones/Instrucciones-05100-05150-05200-05240-ES-EN.pdf>

Ficheros Fotométricos LDT / Photometrics File LDT / Fichier Photométrique LDT

[http://www.jisoiluminacion.es/Ficheros\\_LDT/05200-4000K.ltd.zip](http://www.jisoiluminacion.es/Ficheros_LDT/05200-4000K.ltd.zip)

Ficheros Fotométricos IES / Photometrics File IES / Fichier Photométrique IES

[http://www.jisoiluminacion.es/Ficheros\\_IES/05200-4000K\\_IES.zip](http://www.jisoiluminacion.es/Ficheros_IES/05200-4000K_IES.zip)

*Este producto contiene una fuente luminosa de la clase de eficiencia energética D.*

*This product contains a light source of energy efficiency class D.*

*Ce produit contient une source lumineuse de classe d'efficacité énergétique D.*