

**Ref.**

**55507**

Colección / Collection / Collection	Technical Indoor. PRO Professional LED
Descripción / Description / Description	Downlight LED Basculante Downlight LED Swivel Downlight LED Basculant

**Características Luminaria / Light Data Sheet /  
Caractéristiques de la Luminaire**

Material / Material / Matériau	ABS + Aluminio / ABS+Aluminium / ABS + Aluminium		
Material Difusor / Difusor Material/ Matériau Diffuseur	PMMA		
Acabado Difusor / Diffuser Finish/ Touche Finale du Diffuseur	Ácido / Acid / Acide		
Colores / Colours / Couleurs	90 Blanco Técnico / Technical White / Blanc Technique		
Vatios / Watts / Watts	7W		
Lúmens / Lumens / Lumens	Color T. <sup>a</sup>	Useful Lm	Chip Lm
	3000K	430 lm	798 lm
	4000K	453 lm	840 lm
Grados Apertura / Opening Angle / Angle d'ouverture	100°		
IP	20		
Tiempo de Uso (h/día) / Working Time (h/day) / Temps d'utilisation (h/jour)	12-14		
On/Off	10.000		
Temperatura de Funcionamiento (Ta) / Working Temperature (Ta) / Température de Fonctionnement (Ta)	-20°C to +40°C		
Humedad de Funcionamiento / Working Humidity / Humidité de Fonctionnement	20-90% RH		
Peso / Weight / Poids	0,1 Kg		
Cantidad / Pieces / Quantité	1/ 48		

**Características del Chip / Chip Data Sheet / Caractéristiques de la Puce**

Marca / Brand / Marque	SANAN
Tipo / Type / Type	SMD 2835
L70	15.000 h
SDCM (Mac Adam)	5
EN62471	RG1
Eficiencia Nominal / Nominal Efficiency / Efficacité Nominal	120 Lm/W (4000K)



Compatible lighting with installations that require UGR<19  
Compatible con instalaciones que requieren UGR<19  
Compatible avec les installations nécessitant UGR <19

**Características Driver / Driver Data Sheet / Caractéristiques de l'Alimentateur**

Ref.	Driver	Voltaje de Entrada Input Voltage Tension d'Entrée	FP PF FP	Garantía Warranty Garantie	Flicker
55507-198_-	Dimmable. Trailing Edge	AC220-240V 50/60Hz	>0,85	3	Not Free

Colores / Colours / Couleurs



90 Blanco Técnico / Technical White  
/ Blanc Technique

Accesorios / Accessories / Accessoires



JISO Smart Control



DC553



DC55490




1EH-3



1EH-4

Conexiones / Connections / Connexions



Documentos / Documents / Des documents

Declaración de Conformidad UE / EU Declaration of Conformity / Déclaration de Conformité UE

[http://www.jisoiluminacion.es/CE/CE\\_RECESSED-LUMINAIRES.pdf](http://www.jisoiluminacion.es/CE/CE_RECESSED-LUMINAIRES.pdf)

Instrucciones de Instalación / Installation Instructions / Instructions d'Installation

<http://www.jisoiluminacion.es/Instrucciones/Instrucciones-55307-55507-ES-EN.pdf>

Ficheros Fotométricos LDT / Photometrics File LDT / Fichier Photométrique LDT

[http://www.jisoiluminacion.es/Ficheros\\_LDT/55507.ltd.zip](http://www.jisoiluminacion.es/Ficheros_LDT/55507.ltd.zip)

Ficheros Fotométricos IES / Photometrics File IES / Fichier Photométrique IES

[http://www.jisoiluminacion.es/Ficheros\\_IES/55507.IES.zip](http://www.jisoiluminacion.es/Ficheros_IES/55507.IES.zip)

Este producto contiene una fuente luminosa de la clase de eficiencia energética D.

This product contains a light source of energy efficiency class D.

Ce produit contient une source lumineuse de classe d'efficacité énergétique D.